

# PIN Pad Terminals

## EMV, NFC Contactless, Touch Screen, IP, Wi-Fi & Bluetooth

All Dejavoo PIN Pad Payment Devices are EMV Chip Card Ready and Certified

All come standard with the following features: NFC Contactless Readers for Apple pay, Google Wallet, Samsung Pay, etc. – Different models provide options such as Touch Screen, Bluetooth, WiFi and Mobility! Easy Integration to POS Systems using our SPIn (Secure Payment Integration) development tools or use as a simple USB PIN Pad solution.

**GOGreen**  
Send Electronic Receipts!

EMV Certified



## Z6 Touch Screen USB & IP

Touchscreen and versatile the Z6 PIN Pad terminal is EMV certified and an excellent solution for SPIn (Semi-Integration to a POS System) or as a simple PIN Pad via USB.

Signature on the display and the **GOGreen** electronic receipt option make PIN Pad terminals the ideal option to complete your merchants countertop Needs.

Two operating modes: "Dispatch" – using a Z3-6 as a Pin Pad terminal or a "Simple" Pin Pad – Using the device as a secured Cards reader device obtaining authorizations via Dejavoo Terminals.

Auto Update, CallMe and DeNovo – Available!



 **PSP**  
Card Services Corporation

# Z3 USB & IP



## Features:

- Built In NFC Contactless Reader
- EMV 4.x L1 and L2 Certified
- Ethernet connectivity
- 32 bits high performance secure Microprocessor, @ 400MHz
- 2.4" color LCD (320x240 pixels)
- 192 MB of Memory (128 MB RAM / 64 MB DDR RAM)
- High Security CPU
- Open Architecture Linux Operating System
- PCI PTS v3.x Certified



# Z1 Mobile, BT & WiFi

The Z1 EMV Mobile PIN Pad Terminal Allows Multiple Transaction Entry Points! With its Bluetooth and WiFi capability the Z1 provides security and wide range connection. Small and hand held, this mobile PIN Pad's portability makes it an ideal solution for SPIn (Secure Payment Integration) providing POS Software the EMV Payment security needed in todays market.



| PIN Pad Terminals          |                           | Touch Screen  | Non Touch Screen                                  |
|----------------------------|---------------------------|---|---|
| Processor                  |                           | 32 bits 400 MHz Secure Microprocessor   |   |
| Memory                     | Flash / DDR RAM           | 128 MB/64MB   |   |
|                            | Micro SD Socket           | Optional  |   |
| Display                    |                           | 3.5" Color TFT-LCD ~<br>320X480 Pixels  | 2.4" Color LCD ~<br>320X4240 Pixels               |
| Touch Screen               |                           | ✓   | X   |
| Card Readers               | Magnetic Strip (Standard) |   | ISO 7810, 7811 & 7813 Triple Track Bi-Directional |
|                            | Contact Card              | User Card   | ISO 7816 ID-1 1.8V/3V/5V T=0, T=1                 |
|                            |                           | SAM Card (up to 4)  | 2   |
| Contactless (Standard)     |                           | ISO 14443 Type A, B, ISO 18092 NFC and Milfare® and SONY® Felica ~ Working frequency 13.56MHz                 |   |
| Communications Connections |                           | Ethernet, RS232, USB, WiFi (Z1) & BlueTooth (Z1)  |   |
| Indicator                  | LED – 4 LEDs              | X   | ✓   |
| Keypad                     |                           | 15 Standard Keys  | 15 Standard Keys                                  |
| Function Keys              |                           | X   | 3   |
| Dimensions (L/W/H)         |                           | 5.7" X 3" X 2.2" (Z6 & Z3)  |   |
| Weight                     |                           | .57 lbs (Z6)  | .62 lbs (Z3)                                      |
| Environment                | Operating Temperature     | 32°F to 150°F   |   |
|                            | Storage Temperature       | -4°F to 158°F   |   |
| Certifications             | Security & Payment        | PCI PTS, EMV L1 L2, TQM, PBOC L1 L2<br>Visa PayWave, MasterCard PayPass,<br>American Express, & JCB J/ Speedy |   |
|                            | Safety, EMC               | CE, FCC, BSMI, RoHS   |   |
| Software                   |                           | SDK, KMS, TMS, Simulator, CTOS library,<br>ISO 8583 library, Crypto library                                   |   |
| Crypto                     |                           | TRNG, DES, T'DES, AES, RSA, MK/SK, DUKPT,<br>T'DES DUKPT  |   |



[www.pspcardservices.com](http://www.pspcardservices.com)

400 Applewood Cres. Suite 200, Vaughan ON, L4K 0C3  
Phone: 1-844-780-9293  
Email: support@pspcardservices.com